



AUTO-RANGING



AUTOSPEGNIMENTO  
AUTO POWER OFF



MANEGGEVOLE  
EASY TO HANDLE

## DATI TECNICI TECHNICAL DATA

<b>Tensione DC</b> DC Voltage	200mV, 2V, 20V, 200V, 600V, 1000V
<b>Tensione AC</b> AC Voltage	200mV, 2V, 20V, 200V, 600V, 1000V
<b>Corrente DC</b> DC Current	200µA, 2mA, 20mA, 200mA, 10A
<b>Corrente AC</b> AC Current	200µA, 2mA, 20mA, 200mA, 10A
<b>Resistenza</b> Resistance	200Ω, 2KΩ, 20KΩ, 200KΩ, 2MΩ, 20MΩ
<b>Continuità</b> Continuity	R < 100 Ω
<b>Diodi</b> Diode test	✓
<b>Temperatura</b> Temperature	- 50°C / + 1000°C
<b>Blocco valore/lettura</b> Data hold	✓
<b>Blocco del valore massimo</b> Max hold	✓
<b>Autospegnimento</b> Auto power off	15 min
<b>Classe di funzionamento</b> Measurement category	Cat. III 600V Cat. II 1000V
<b>Alimentazione</b> Power supply	1 x 9V batteria non include battery not included



### CARATTERISTICHE

Autoranging, selezione automatica della scala di misura  
Protetto da fusibile interno  
Data Hold,  
Autospegnimento dopo 15 minuti

### ESEGUE LE SEGUENTI MISURE:

Tensione (AC/DC) fino a 1000V  
Corrente (AC/DC) fino a 10A  
Resistenza  
Prova Diodi  
Prova Continuità con indicazione acustica  
Temperatura (-50°C/+1000°C) con termocoppia

### FEATURES

- Autoranging, automatic selection of the measuring scale
- Protected by internal fuse
- Data hold,
- Auto power-off after 15 minutes

### MEASUREMENTS:

- Voltage (AC/DC) up to 1000V
- Current (AC/DC) up to 10A
- Resistance
- Diode test
- Continuity test with audible signal
- Temperature (-50°C/+1000°C) with thermocouple



CONFEZIONE  
12 PEZZI  
12 PCS  
BOX

